

PLIO® membrane grommets DG in flexible PVC



PLIO®




DG-PVC

Material: flexible polyvinyl chloride
Colours: black - light grey (RAL 7035)
Operating temperatures: -30 to +70°C
Hardness Shore A: 55 ± 5
Tensile strength at break: 8 MPa
Ultimate elongation: > 250 %
Dielectric strength: > 20 kV/mm
Specification: HB UL94
Application: closure of unused entries.
 They allow the passage of cables or conduits through the membrane by ensuring a dust free fit.



• Membrane grommets

type	article number		dimensions (mm)								
	black 010	grey 025	Ø A	Ø B	Ø C1	Ø C2	D	F1	F2	M	
DG-PVC 9	0133 0351 010	0133 0351 025	9	15	20	18	2	2,5	2,5	1	100
DG-PVC 11	0133 0352 010	0133 0352 025	11	18	22,5	21,5	2	2,5	2,5	1	100
DG-PVC 13,5	0133 0353 010	0133 0353 025	13,5	20	24	24	2	2,5	2,5	1	100
DG-PVC 16	0133 0354 010	0133 0354 025	16	22	27,5	26	2	2,7	2,7	1	100
DG-PVC 16/E3	0133 0360 010	-	16	22	27,5	26	3	2,7	2,7	2	100
DG-PVC 21	0133 0355 010	0133 0355 025	21	28	34,5	34,5	2	3	3	1	100
DG-PVC 21/E1	0133 0359 010	-	21	28	34,5	34,5	1	4	3	1,2	100
DG-PVC 29	0133 0356 010	-	29	36,5	43	43	2,2	3,7	3,7	1,5	50
DG-PVC 36	0133 0357 010	-	35	46	52,5	52,5	2,5	3,8	3,8	1,3	50
DG-PVC 48	0133 0358 010	-	46,5	59	66,2	66,2	2,5	4	4	1,6	50
DG-PVC M20	0133 0510 010	0133 0510 025	13,5	20	24	24	2	2,5	2,5	1	100
DG-PVC M25	0133 0511 010	0133 0511 025	21	25	34,5	34,5	2	3	3	1	100
DG-PVC M32	0133 0512 010	0133 0512 025	29	32	43	43	2	3,5	3,5	1,5	100



• Cross-cut membrane grommets (other cut-outs possible upon request)

type	article number	dimensions (mm)									
	010	Ø A	Ø B	Ø C1	Ø C2	D	F1	F2	X	M	
DGC-PVC 9	0133 0451 010	9	15	20	18	2	2,5	2,5	8	1	100
DGC-PVC 11	0133 0452 010	11	18	22,5	21,5	2	2,5	2,5	10	1	100
DGC-PVC 13,5	0133 0453 010	13,5	20	24	24	2	2,5	2,5	10	1	100
DGC-PVC 16	0133 0454 010	16	22	27,5	26	2	2,7	2,7	14	1	100
DGC-PVC 21	0133 0455 010	21	28	34,5	34,5	2	3	3	17	1	100
DGC-PVC 21/E1	0133 0456 010	21	28	34,5	34,5	1	4	3	19,5	1,2	100
DGC-PVC 29	0133 0457 010	29	36,5	43	43	2,2	3,7	3,7	25	1,5	50
DGC-PVC 36	0133 0458 010	35	46	52,5	52,5	2,5	3,8	3,8	32	1,3	50
DGC-PVC 48	0133 0464 010	46,5	59	66,2	66,2	2,5	4	4	42	1,6	50

